





- Engineered for the power and durability required for use with light gauge steel
- Accepts large head (nominal 5/16" diameter) pins for maximum pull over resistance
- Fingertip adjustable depth control to precisely place pin at desired depth
- Power to fasten to 20 ga to 14 ga steel at the speed of fastening to wood
- Operates using typical jobsite air compressor at 120 psi maximum
- Sequential fire actuation for accurate pin placement
- Capable of driving pins 1-1/2" to 2-1/2" long
- ET&F's most versatile tool


CONTACT & SERVICE

 LIGHT TRIM
Siding Solutions
 P +1418 914 8053
 E info@lighttrim.com
 W www.lighttrim.com

PIN TYPE
AGS-100 PANELFAST®PINS

Panelfast®Model 510A

TOOL CHARACTERISTICS

Height	Width	Length	Weight
11.69 inch	5.27 inch	10.38 inch	6.01lbs
297 mm	134 mm	264 mm	2.7 kg

Pressure 70 - 120 psi | 5 - 8 bar
 Lubricant Non-detergent pneumatic tool lubricant

Recommended steel thickness
 20 ga - 14 ga



FASTENER DATA

Pin Type	AGS-100-0150NA	AGS-100-0200NA	AGS-100-0250NA
Wire	0.100" 2.54 mm		
Shank	Knurled		
Head	Nominal 5/16" 8 mm		
Length	1 1/2" 39 mm	2" 50 mm	2 1/2" 63 mm
Coating	Aericoate®1000		
Magazine Capacity	250 pins/coil		

ACTUATION & LOADING

Actuation System: Sequential Fire
 Loading: Coil

AIR CONSUMPTION PER SHOT

0.077 SCF | 2.2 L
 Performance at 87 psi / 6 bar (0.7MPa)

APPLICATIONS

- HardiePlank®fiber cement siding to steel framing (ICC ES ESR-2290)
- Wood sheathing and wood structural panel diaphragms to steel framing (IAPMO ES ER-335)
- Wood structural panel shear walls to steel framing (ICC ES ESR-1777)
- DensGlass®Gold to steel framing (ICC ES ESR-2398)
- Stucco lath to steel framing
- Rigid foam insulation to steel framing
- Vinyl siding to steel framing